



STANDARD

Base in AISI 304 stainless steel | Display area in AISI 304 stainless steel | Exterior decoration in skinplate | AISI 304 stainless steel worktop | Chassis in AISI 304 stainless steel | Exterior back-end in AISI 304 stainless steel | Polyurethane injected sides | Multiplexible | Ventilated refrigeration | LED lighting | Digital thermometer | Electronic temperature controller | Programmable automatic defrosting | Treated evaporator | Tilting front glass | Tempered glasses | Adjustable stainless steel feet

OPTIONS

Quartz worktop | Exterior decoration in painted plate (RAL) | Exterior decoration in AISI 304 stainless steel | Electric evaporation of the evaporator defrost water | Reversible fan motors | Sliding rear doors | Supplementary shelves level without lighting | Supplementary shelves level with lighting | Front glass anti-condensation system | Additional socket | Castors with brakes | Adjustable stainless steel high feet | Voltage 115 V-60 Hz / 120 V-60 Hz / 220 V-60 Hz



Ventilated



0/4 °C




Automatic



LED



230V | 1 Ph | 50 Hz



M1 | 25 °C | 60% R.H.



Plug-in



R290 ECO Friendly

C100 VA 70S	100	130	150	200	250	300
Operating temperature	0/4 °C	0/4 °C	0/4 °C	0/4 °C	0/4 °C	0/4 °C
Refrigerant (ref/GWP)	R290/3	R290/3	R290/3	R290/3	R290/3	R290/3
Defrost	Tempo	Tempo	Tempo	Tempo	Tempo	Tempo
External dimensions (LxDxH) (mm)	1025x1100x1254	1325x1100x1254	1525x1100x1254	1970x1100x1254	2570x1100x1254	2970x1100x1254
TDA - Total display area (m ²)	0,82	1,02	1,15	1,45	1,85	2,12
Net volume (l)	172	226	262	343	452	525
Refrigerated shelf area (m ²)	0,77	1,01	1,17	1,53	2,02	2,34
Insulation	PUR/H2O	PUR/H2O	PUR/H2O	PUR/H2O	PUR/H2O	PUR/H2O
Nominal power (W)	1107	1073	1085	1398	1455	1474
Electric current (A)	5	5,2	5,3	6,8	7,2	7,2
TEC - Total energy consumption (kWh/24h)	5,452	5,961	6,150	6,621	7,452	7,973
AEC - Annual energy consumption (kWh/annum)	1989,98	2175,77	2244,75	2416,30	2719,98	2910,15
Energy efficiency class*						

* The information presented regarding the energy class (Energy Labeling regulation and Eco Design regulation) is only related to the standard models. For the energy class of the equipments with different options that involve elements of energy consumption and/or changes in the construction of the unit, please contact the manufacturer directly.
 ** Pictures and colors are not contractual. The information presented refers to the standard equipments in plug-in version. For additional information about remote our neutral units, contact the manufacturer.

