



STANDARD

2 sliding doors | Dual temperature cooling/freezing | Lateral triple glasses | Display area in skinplate | Exterior decoration in skinplate | Ventilated refrigeration | Bumper | LED lighting | Digital thermometer | Electronic temperature controller | Programmable automatic defrosting | Automatic evaporation of defrost water | Castors with brakes

OPTIONS

Reversible fan motors | Voltage 115 V-60 Hz / 120 V-60 Hz / 220 V-60 Hz



Ventilated



-21/-18 °C | 0/4 °C



Automatic



LED



230V | 1 Ph | 50 Hz






L1/M1 | 25 °C | 60% R.H.



Plug-in



R290 ECO Friendly

CAYO	100	150	200
Operating temperature (°C)	-21/-18 °C 0/4 °C	-21/-18 °C 0/4 °C	-21/-18 °C 0/4 °C
Refrigerant (ref/GWP)	R290/3	R290/3	R290/3
Defrost	Electric	Electric	Electric
External dimensions (LxDxH) (mm)	1042x1095x1021	1542x1095x1021	1975x1095x1021
TDA - Total display area (m ²)	1,60	2,26	2,83
Net volume (l)	203	314	410
Refrigerated shelf area (m ²)	0,77	1,19	1,55
Insulation	PUR/H2O	PUR/H2O	PUR/H2O
Nominal power (W)	576	1109	1142
Electric current (A)	2,92	5,65	5,79
TEC - Total energy consumption (kWh/24h)	8,000 3,267	11,247 4,887	14,257 7,154
AEC - Annual energy consumption (kWh/annum)	2920,00 1192,46	4105,16 1783,76	5203,81 2611,21
Energy efficiency class*			

* The information presented regarding the energy class (Energy Labeling regulation and Eco Design regulation) is only related to the standard models. For the energy class of the equipments with different options that involve elements of energy consumption and/or changes in the construction of the unit, please contact the manufacturer directly.
 ** Pictures and colors are not contractual. The information presented refers to the standard equipments in plug-in version. For additional information about remote our neutral units, contact the manufacturer.

