



STANDARD

2 sliding doors | Dual temperature cooling/freezing | Low emissions tempered glass | Display area in skinplate | Exterior decoration in skinplate | Ventilated refrigeration | Bumper | LED lighting | Digital thermometer | Electronic temperature controller | Programmable automatic defrosting | Automatic evaporation of defrost water | Castors with brakes

OPTIONS

Reversible fan motors | Voltage 115 V-60 Hz / 120 V-60 Hz / 220 V-60 Hz



Ventilated



-21/-18 °C | 0/4 °C



Automatic



LED



230V | 1 Ph | 50 Hz



L1/M1 | 25 °C | 60% R.H.







Plug-in



R290 ECO Friendly

HYCE **150** **200**

Operating temperature (°C)	-21/-18 °C 0/4 °C	-21/-18 °C 0/4 °C
Refrigerant (ref/GWP)	R290/3	R290/3
Defrost	Electric	Electric
External dimensions (LxDxH) (mm)	1507x1099x899	1977x1099x899
TDA - Total display area (m ²)	1,00	1,37
Net volume (l)	245	331
Refrigerated shelf area (m ²)	1,11	1,51
Insulation	PUR/H2O	PUR/H2O
Nominal power (W)	825	1082
Electric current (A)	3,84	4,49
TEC - Total energy consumption (kWh/24h)	8,487 4,332	9,790 3,632
AEC - Annual energy consumption (kWh/annum)	3097,76 1581,18	3573,35 1365,32
Energy efficiency class*	 	 

* The information presented regarding the energy class (Energy Labeling regulation and Eco Design regulation) is only related to the standard models. For the energy class of the equipments with different options that involve elements of energy consumption and/or changes in the construction of the unit, please contact the manufacturer directly.
 ** Pictures and colors are not contractual. The information presented refers to the standard equipments in plug-in version. For additional information about remote our neutral units, contact the manufacturer.

