



STANDARD

Display area in skinplate | Exterior decoration in skinplate | Sides in lacquered MDF (RAL) | Ventilated refrigeration | LED top lighting | Electronic temperature controller | Programmable automatic defrosting | Electric evaporation of defrost water | Double-glass sides | Tempered glasses | Adjustable feet | Night curtain

OPTIONS

Display area in painted plate (RAL) | Display area in AISI 304 stainless steel | Exterior decoration in painted plate (RAL) | Exterior decoration in AISI 304 stainless steel | Treated evaporator | Additional shelf without lighting | Additional socket | Castors with brakes | Voltage 115 V-60 Hz / 120 V-60 Hz / 220 V-60 Hz



Ventilated



0/4 °C



Automatic



LED



230V | 1 Ph | 50 Hz



M1 | 25 °C | 60% R.H.



Plug-in



R290 ECO Friendly

UNDERCOUNTER	100	130	150
Operating temperature	0/4 °C	0/4 °C	0/4 °C
Refrigerant (ref/GWP)	R290/3	R290/3	R290/3
Defrost	Time	Time	Time
External dimensions (LxDxH) (mm)	911x928x1085	1236x928x1085	1516x928x1085
TDA - Total display area (m ²)	0,64	0,88	1,08
Net volume (l)	95	136	170
Refrigerated shelf area (m ²)	0,44	0,61	0,76
Insulation	PUR/H2O	PUR/H2O	PUR/H2O
Nominal power (W)	1404	1357	1658
Electric current (A)	6,43	6,85	8,22
TEC - Total energy consumption (kWh/24h)	11,954	13,245	16,231
AEC - Annual energy consumption (kWh/annum)	4363,21	4834,43	5924,32
Energy efficiency class*			

* The information presented regarding the energy class (Energy Labeling regulation and Eco Design regulation) is only related to the standard models. For the energy class of the equipments with different options that involve elements of energy consumption and/or changes in the construction of the unit, please contact the manufacturer directly.
 ** Pictures and colors are not contractual. The information presented refers to the standard equipments in plug-in version. For additional information about remote our neutral units, contact the manufacturer.

